

LPS® CFC FREE



产品特性

- 适用于电气/电子和精细零件
- 清洁和去除精致的精密机制
- 渗透作用可去除油、油脂、污垢、助焊剂和其他污染物
- 不含氯化溶剂
- 快速挥发
- 无残留&塑料表面安全使用
- 认证标准: McDonnell Douglas CSD #1; AMS 1525B; ASTM F-519, Type 1c; MIL-PRF-29608 Section 3.6 Type C
- Inverta 喷雾阀可让您以直立或倒置的方式喷涂

包装规格

净含量

11 wt. oz. / 312 g/ 459 mL (气溶胶)
1 gal. (3.78 L)
5 gal. (18.93 L)
55 gal. (208 L)

产品代码

03116
03101
03105
03155

产品应用

- 缆绳
- 断路器
- 电动机
- 电子连接器
- 发电机
- 铰链
- 点火系统
- 锁
- 千分尺
- 精密开放式齿轮
- 电动工具
- 继电器
- 滑动机制
- 开关齿轮



Nonfood Compounds Program Listed
Category Code: K2 Registration # 059813
(Aerosol); # 059814 (Bulk)



产品性能

闪点:

<0°F (<-18°C)

不挥发百分比 (%) :

约 50 ppm

HCFC 物质百分比 (%) :

0%

KB值:

:31

比重:

0.665

表面张力:

17.3 dynes/cm @

77°F (25°C)

助推剂:

Carbon Dioxide

VOC:

100%, 665 g/L,

5.55 lbs./gal.(桶装)

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE :WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2012 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2068 • Rev. 5/2012